



HEAVY DUTY MIXED FLEET LIFETIME ANTIFREEZE/COOLANT PRE-MIX 50/50

PowerGard™ Fleet Heavy Duty Antifreeze/Coolant is a Nitrite, Amine, Phosphate, Borate, Molybdate and Silicate free Polyorganic coolant. This is sometimes referred to as a NAPS Free coolant and if properly maintained will likely last the life of your diesel engine or passenger vehicle.

ADVANTAGES

- Will provide up to 750,000 miles or 6 years of service life protection in heavy duty diesel use if properly maintained
- Fully compatible with other OAT extended life coolants as long as they meet ASTM standards
- A preferred choice where mixed fleets or light duty and heavy duty applications are needed
- No SCAs or chemical filters are needed. An added cost savings for end-users
- Designed for superior performance in wet sleeve liner cavitation protection, as well as corrosion/erosion protection of all metals
- Blended with pure deionized water
- Includes bittering agent in all packages meeting all North American acceptable ranges





PowerGard™ Fleet will provide outstanding performance in the following applications:

- ASTM 6210
- ASTM 3306
- Case New Holland™
- Caterpillar™
- Chrysler™
- Cummins™
- Detroit Diesel™
- Ford™
- Freightliner™
- GM Dex-Cool™
- GMC Truck™
- International Truck™
- John Deere™
- Kenworth™
- Mack Trucks™
- Navistar™
- Paccar™
- Peterbilt™
- Thermo-King™
- TMC RP 329
- US Military A-A 52624-A
- Volvo™

TYPICAL PROPERTIES

DESCRIPTION	TEST NUMBER	VALUE
Specific gravity	D-1122	1.231
Freeze Point 50% B/V	D-3321 or D-1177	-34° F
Boiling Point 50% B/V	D-1120	265° F – 15# Cap
Reserve Alkalinity	D-1121	5.5
Foam Test	D-1881	80 ml / 2.0 sec max
Color	Visual	Yellow or Red

Available in Drums, Totes, Bulk and Gallon Jugs



MEG 2, LLC
11210 Solomon Road
Troy, In, 47588
812.547.7951

Are Trademarks of MEG 2, LLC