



**CONVENTIONAL  
GREEN 50/50**

## **PowerGard™ Premium Green 50/50 AntiFreeze**

Is a premium ethylene glycol based antifreeze that provides all season protection and when used as directed, offers superior 5-way protection against:

- Freeze-up/Boil Over
- Scale Build-up
- Sludge/Clogging
- Wet Sleeve Liner Pitting
- Rust Corrosion

### **ADVANTAGES**

- Meets Light Duty ASTM D-3306 and Heavy Duty ASTM D-6210
- One product for Light Duty and Heavy Duty Applications
- No need to add SCAs or chemical filters
- Blended with pure deionized water for your quality concerns
- Compatible with all Conventional Green Antifreeze
- Phosphate free and meets low silicate standards
- May be used in virtually any engine cooling system
- Light Duty - 5 years/150,000 miles
- Heavy Duty - 3 years/300,000 miles
- For safety – All PowerGard Antifreeze contains a bittering agent

### **SPECIFICATIONS**

As an all purpose, conventional antifreeze, PowerGard Green 50/50 is blended with proprietary additives designed to safely meet the performance specifications of (but not limited to):

- ASTM D-3306
- Ford ESE M97B44D
- Chrysler MS 7170
- GM 1825M
- GM 1899M
- ASTM D-6210
- Caterpillar
- GMC Truck
- John Deere
- Case
- Mack
- Detroit Diesel
- GE Locomotive
- Military CID
- A-A52624-A
- Orion/ MCI
- Coaches
- Freightliner
- International
- TMC RP329



### **TYPICAL PROPERTIES**

DESCRIPTION	TYPICAL VALUES	TEST METHOD
Appearance	Visual	Green
Specific Gravity at 60/60°F	1.053-1.083	D 1122
Freeze Point, at 50% max	-34°F	D-3321
pH at 50% Solution	8.5-10.0	D-1287
Reserve Alkalinity min.	2.5	D-1121
Foam Test	150ml/5 sec	D-1881

BOIL OVER PROTECTION			
Type of Coolant Test	Atmospheric Pressure	14 LB. cap	15 LB. cap
Coolant Boiling	224°F	262°F	265°F
Coolant Freezing	-34°F	-34°F	-34°F

**Available in Gallon Jugs, Drums, Totes and Bulk**



MEG 2, LLC  
11210 Solomon Road  
Troy, In, 47588  
812.547.7951

Are Trademarks of MEG 2, LLC