



**HEAVY DUTY MIXED-FLEET
LIFETIME 50/50**

PowerGard™ Fleet Heavy Duty 50/50 AntiFreeze

is a Nitrite, Amine, Phosphate, Borate, Molybdate and Silicate free Polyorganic coolant. This is sometimes referred to as a NAPS Free coolant and if properly maintained will likely last the life of your diesel engine or passenger vehicle.

ADVANTAGES

- Will provide up to 750,000 miles or 6 years of service life protection in heavy duty diesel use if properly maintained
- Fully compatible with other OAT extended life coolants as long as they meet ASTM standards
- A preferred choice where mixed fleets or light duty and heavy duty applications are needed
- No SCAs or chemical filters are needed. An added cost savings for end-users
- Designed for superior performance in wet sleeve liner cavitation protection, as well as corrosion/erosion protection of all metals
- Blended with pure deionized water
- Includes bittering agent in all packages meeting all North American acceptable ranges



PowerGard™ Fleet will provide outstanding performance in the following applications:

- ASTM 6210
- ASTM 3306
- Case New Holland™
- Caterpillar™
- Chrysler™
- Cummins™
- Detroit Diesel™
- Ford™
- Freightliner™
- GM Dex-Cool™
- GMC Truck™
- International Truck™
- John Deere™
- Kenworth™
- Mack Trucks™
- Navistar™
- Paccar™
- Peterbilt™
- Thermo-King™
- TMC RP 329
- US Military A-A 52624-A
- Volvo™

TYPICAL PROPERTIES

DESCRIPTION	TEST NUMBER	VALUE
Specific gravity	D-1122	1.231
Freeze Point 50% B/V	D-3321 or D-1177	-34° F
Boiling Point 50% B/V	D-1120	265° F – 15# Cap
Reserve Alkalinity	D-1121	5.5
Foam Test	D-1881	80 ml / 2.0 sec max
Color	Visual	Yellow or Red

**Available in Gallon Jugs,
Drums, Totes and Bulk**



Are Trademarks of MEG 2, LLC

MEG 2, LLC
11210 Solomon Road
Troy, In, 47588
812.547.7951